

ALL INDIA INSTITUTE OF MEDICAL SCIENCES, DEOGHAR अखिलभारतीयआयुर्विज्ञानसंस्थान, देवघर INSTITUTE OF NATIONAL IMPORTANCE UNDER MINISTRY OF HEALTH AND FAMILY WELFARE

स्वास्थ्यऔरपरिवारकल्याणमंत्रालयकेअंतर्गतराष्ट्रीयमहत्वकीसंस्थान)(

Invitation of Quotation

For

Plumbing work of Blood Bank Center at AIIMS Deoghar.

Reference No.: AIIMS/Deoghar/Engineering/NIQ / 2025-26/15

Date of Issue: 04/10/2025

Last Date of Submission: 10/10/2025

All India Institute of Medical Sciences, Deoghar: 814152, Jharkhand

email: engineering@aiimsdeoghar.edu.in

Reference no: AIIMS/Deoghar/Engineering /NIQ/ 2025-26/15

Invitation of Quotation for Plumbing work of Blood bank center at AlIMS Deoghar.

Sealed Quotations are invited on behalf AlIMS, Deoghar for Plumbing work of Blood bank centre at AIIMS Deoghar (Annexure-I) required for the Institute as per terms & conditions mentioned below. The filled quotations along with all the required documents must reach in the office of the undersigned on or before 10/10/2025 at 04:00 PM. The Envelope containing the quotation must be sealed and super scribed as under: -

"QUOTATION For Plumbing work of Blood Bank Centre at AIIMS Deoghar

FOR REFENRENCE NO.: AIIMS/Deoghar/ Engineering / NIQ/ 2025-26/15, Due on 10/10/2025 at 04.00 PM"

The Envelope containing the quotation must be sent to:

Superintending Engineer **AIIMS Deoghar** Jharkhand: 814152

1. Terms & Conditions:

a) The quotations received after this deadline or unsealed shall not be entertained under any circumstances whatsoever. In case of postal delay this Institute will not be responsible. The offer submitted by Fax / email shall not be considered and no correspondence will be entertained in this matter.

- b) Quotations must be in the enclosed prescribed Performa (Annexure -2) on the letter head of the firm duly signed by the Proprietor/ Partner/ Director or their authorized representative, in case of signing of quotation by the authorized representative letter of authorization must be attached with the quotation.
- c) The supplier should supply all the equipment's / items along with its accessories.
- d) Rates must be quoted in Indian rupees.
- e) Rates must be inclusive of all charges (including Freight charges, Insurance, installation, taxes etc.).
- f) **No overwriting or cutting** is permitted in the rate. If found, the quotation shall be summarily rejected.
- g) The rates quoted must be valid for 90 days minimum from the date of opening of the quotation and silence of any tendered on this issue shall be treated as agreed with this condition.
- h) Total cost/amount will be taken in consideration for L1. Becoming L1 will not be the criteria for awarding of purchase order unless the rates are reasonable & justified.
- i) The firm / agency may satisfy the following conditions and attach self-attested copy of the same with the quotation: -
- The firm shall have valid GST / Other taxes and IT PAN.
- The firm should not be black listed by any Government agency/Department.
- Similar work experience certificate. Similar work means work related to Building construction / Maintenance, Plumbing work.
- j) Quotations qualified by such vague and indefinite expressions such as "subject to prior confirmation", "subject to immediate acceptance" etc. will be treated as vague offers and it will be rejected accordingly. Any conditional quotation shall be rejected summarily.
- k) The Bidders who have not obeyed the previous work order will not be allowed to participate in the NIQ.
- I) Liquidated Damage: If the supplier fails to deliver the material / complete the work on or before the stipulated date, then a penalty at the rate of 0.5 % per week of the total order value shall be levied subject to maximum of 10% of the total order value.
- m) Payment Terms: Payment will be only released after successful completion of work.
- n) **Disputes:** -In the event of any dispute or disagreement arising between the contractors and any other department of AIIMS Deoghar with regards to the interpretation of "Terms & Conditions" of this inquiry, the same shall be referred to arbitrator appointed by The Executive Director, AIIMS, Deoghar, whose decision will be final and binding upon the contractor.
- o) AIIMS, Deoghar reserves the right to increase or decrease quantity. Decision of Quantity of items in the AIIMS, Deoghar will be final in this regard.
- p) AIIMS, Deoghar reserves the right to reject any quotation or part or the whole of inviting quotation process without assigning any reason. Decision of The Executive Director, AIIMS, Deoghar, will be final in this regard.
- q) The envelope containing quotation should be sealed with wax/ tape from both the sides. No quotation will be accepted if received after due date.

Executive Engineer (c)
AIIMS Deoghar

TERMS AND CONDITIONS:

- 1. The work should be carried out strictly as per the specifications and as per the directions of the Engineer-in-charge.
- 2. Safety measures as specified in CPWD general conditions of contract should be adopted to protect the labour from every risk.
- 3. Before tendering, the contractor shall inspect site of work and shall fully acquaint himself about the conditions prevailing at site, availability of materials in market, availability of ready site and suitable locations for execution of the work involved in achieving the completion of work.
- 4. The contractor shall at his own expense and risk arrange the storage of materials at site of the work for carrying out of all jobs connected with the completion of the work. The contractor shall have to abide by the regulations of the authorities concerned and the directions of the I/c Engineering Section. If during construction, it becomes necessary to remove or shift the equipment, material, etc, to facilitate execution, the contractor shall carry out the removal of shifting as directed by the Executive Engineer and re-shift to its original position and no claim whatsoever, shall be entertained on this account.
- 5. It shall be deemed that the contractor has satisfied himself as to the nature and location of the work, transport facilities, availability of site, etc. the department will bear no responsibility for lack of such knowledge & the consequences thereof.
- 6. The Incharge Engineering Section shall have full powers for removal of any or all of the materials brought to site by contractor which are not in accordance with the contract specifications or do not confirm, in character or quality. In case of default on the part of the contractor in removing rejected materials, the Officer-in-charge shall be at liberty to have them removed at the risk and cost of the contractor.
- 7. The work shall be carried out in such a manner so as not to interfere / or adversely / or disturb the functioning of the Institute and other works being executed by other agencies, if any.
- 8. Any damage done by the contractor to any existing work or work being executed by other agencies shall be made good by him at his own cost.
- 9. The contractor shall maintain in good condition all work executed till the completion of entire work entrusted to the contract under this contract.
- 10. No payment shall be made to the contractor for damage caused by rain, flood and other natural calamities whatsoever during the execution of works and any damage to the work on this account shall have to be made good by the contractor at his own cost.
- 11. The Contractor shall take instructions from the Incharge Engineering Section regarding collections and stacking of materials at site.
- 12. The Contractor shall be responsible to arrange at his own cost all necessary tools and tackles required for execution of the works including incidental original and maintenance works.
- 13. Before starting the work submit the sample of respective work to engineering section and take the approval.

- 14. The University shall not be responsible for any injury partial or permanent or death of any workers at site due to accident or malfunctioning of the equipment or by negligence of the Contractors staff on site.
- 15. All applicable and prevailing taxes will be recovered from the bills as applicable from time to time.
- 16. If any damage caused for public conveniences/ services, the same shall have to be repaired instant, failing which necessary recovery shall be make from the bill.
- 17. If any Building, Road and Channels will be damaged by the Contractor the same will have to repair by the Contractor at his risk and cost, otherwise the complete cost will be recovered as intimated by the Engineer-in-charge.
- 18. Price should be inclusive of all (transportation up to AIIMS Deoghar and all other incidental expenditure, if any).
- 19. Price of the items, GST% should be indicated separately.
- 20. No advance payment will be made.
- 21. Verbal quotation or incomplete quotation will be rejected.
- 22. Any variation in the specification(s) during repair/servicing will be rejected.
- 23. Time allowed is 30 days and starts from the date of issue of Work Order. In case of delay in completion of the contract, Liquidate damages (LD) at one percent of the contract value per week of delay subject to a maximum of ten percent of contract value shall be levied
- 24. The work shall be carried out to the entire satisfaction of the Engineering incharge of AIIMS Deoghar.
- 25. Payment shall be made on submission of Invoice after satisfactory execution of the work and as per actual measurements
- 26. The rates quoted are net and nothing extra shall be paid on any account.
- 27. The tax as applicable shall be deducted from the gross amount of the bill.

Harl

Reference no.

Date:

[Letter head of firm] PRICE BID FORM

To
The Superintending Engineer
AIIMS Deoghar
Jharkhand: 814152

Dear	Sir,	I/We		am/are	submitting	the	quotation	for	reference	"For
Pluml	oing	work	of Blood bank centre at	: "AIIMS	DEOGHAR					

FOR REFENRENCE NO.: AIIMS/Deoghar/ Engineering / 2025-26/15, Due on 10/10/2025 at 04.00 PM".

- 1. I/We have thoroughly examined, understood and accepted terms & conditions given in the enquiry document, failing which my quotation will be rejected out rightly.
- 2. I/We hereby offer to supply/install at the following rates:

	Plumbing work of Blood Bank Center at AIIMS Deoghar					
Item No.	Description of Item	Unit	Quantity	Rate	Amount	
1	Providing and fixing wash basin with C.I. brackets, 15 mm dia CP Brass single hole basin mixer of approved quality and make, including painting of fittings and brackets, cutting and making good the walls wherever required:-					
1.1	White Vitreous China Wash basin size 550x400 mm with a 15 mm CP Brass single hole basin mixer	each	4.00			
2	Providing and fixing PTMT Waste Coupling for wash basin and sink, of approved quality and colour.	A . *				
2.1	Waste coupling 38 mm dia of 83 mm length and 77 mm breadth, weighing not less than 60 gms	each	4.00		3	
3	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.					
3.1	Flexible pipe					
3.2	40 mm dia	each	4.00			
4	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors	-		,		
4.1	100 mm inlet and 100 mm outlet					
4.1.1	Sand cast iron S&S as per IS: 3989	each	4.00			
5	Providing and fixing C.P. brass angle valve for basin mixer and gyser points of approved quality conforming to IS:8931		,			
5.1	15 mm nominal bore	each	8.00		7	

Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. 6.1 Concealed work, including cutting chases and making good the walls etc. 6.1.1 Is mm nominal dia Pipes Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply and all CPVC plains brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 7.1 So mm nominal dia Pipes Providing and laying S&S centrifugally cast (spun) iron pipes (class LA) conforming to IS:1536: 8.1 100 mm dia pipe Meter 100.00 Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing CP. brass long body bib cock of approved quality 11.1 15 mm nominal bore Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. 13.1 For thickness of tiles/eranite 10 mm to 25 mm			The second			
6.1.1 15 mm nominal dia Pipes Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 7.1 50 mm nominal dia Pipes Providing and laying 5&S centrifugally cast (spun) iron pipes (Class LA) conforming to IS:1536: 8.1 100 mm dia pipe Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/grante work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	6	(CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per				
Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 7.1 50 mm nominal dia Pipes Providing and laying S&S centrifugally cast (spun) iron pipes (Class LA) conforming to IS:1536: 8.1 100 mm dia pipe Meter 100.00 Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing C.P. brass long body bib cock of approved quality or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore acach 4.00 Providing and fixing C.P. brass long body bib cock of approved quality or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore acach 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/grante work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	6.1					
pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 7.1 50 mm nominal dia Pipes Providing and laying S&S centrifugally cast (spun) iron pipes (Class LA) conforming to IS:1536: 8.1 100 mm dia pipe Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	6.1.1	15 mm nominal dia Pipes	Meter	100.00	<u>L</u>	
7.1 50 mm nominal dia Pipes 8	7	pipes, having thermal stability for hot & cold water supply and all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in				
8 Providing and laying S&S centrifugally cast (spun) iron pipes (Class LA) conforming to IS:1536: 8.1 100 mm dia pipe Meter 100.00 9 Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Each 4.00 Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 12.0 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.		Internal work - Exposed on wall				
Class LA) conforming to IS:1536: 8.1 100 mm dia pipe Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 12.0 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	7.1	50 mm nominal dia Pipes	Meter	100.00		
9 Providing and fixing unplasticized PVC connection pipe with brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Each 4.00 Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 12.0 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	8					
brass unions: 9.1 45 cm length 9.1.1 15 mm nominal bore Each 4.00 Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	8.1	100 mm dia pipe	Meter	100.00		
9.1.1 15 mm nominal bore Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	9				70 6 71	
Providing and fixing white vitreous China pedestal for wash basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	9.1	45 cm length				
basin completely recessed at the back for the reception of pipes and fittings. 10.1 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	9.1.1	15 mm nominal bore	Each	4.00		
High or low pressure, with plastic floats complete: 10.1.1 15 mm nominal bore each 4.00 11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	10	basin completely recessed at the back for the reception of	each	4.00		
11 Providing and fixing C.P. brass long body bib cock of approved quality 11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Cum 4.29 Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	10.1					
11.1 15 mm nominal bore each 4.00 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Cum 4.29 Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	10.1.1	15 mm nominal bore	each	4.00		
Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Cum 4.29 Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	11					
12.0 means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 12.1 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) Cum 4.29 Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	11.1	15 mm nominal bore	each	4.00		
Dismantling tile/granite work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.	12.0	means including disposal of material within 50 metres lead as				
cement mortar including stacking material within 50 metres lead.	12.1		Cum	4.29		* * * * * * * * * * * * * * * * * * * *
13.1 For thickness of tiles/granite 10 mm to 25 mm sgm 18.60	13	cement mortar including stacking material within 50 metres	, , ,		2 .	
7,8 2446 25 11111	13.1	For thickness of tiles/granite 10 mm to 25 mm	sqm	18.60		

Hay

14	Providing and fixing 18 mm thick gang saw cut, mirror polished, remoulded and repolished machine cut granite stone of any colour and shade in flooring, laid over 20 mm thick base cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels				
14.1	Granite stone slab of all colour and texture as per Site requirement & as per direction of engineer-in-charge.	-			
14.1.1	Area of slab over 0.50 sqm	sqm	15.00		
15	Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including finishing complete so as to make it leak proof.	each	8		
16	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:	* 1 A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		*	
16.1	1:1 1/2:3 (1 Cement 1 1/2 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	Cum	4.29		
17.0	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying:				
17.1	(a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours.				
17.1.1	(b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours.				
17.1.1.1	The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.	sqm	18.60		
18.0	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.				

18.1	Size of Tile 500x500 mm	Sqm	3.60		
19	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drain (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, surplus excavated soils as directed, within a lead of 50 m.				
19.1	All kinds of soil	m³	12.00	P 22	
20	Filling available executed earth (excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20 cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 and for all lift.	m³	12.00		
	Total Amount			,	

Note:-

- The bidder must quote their quotation only in above said format on the letter of firm otherwise quotation will be REJECTED.
- Catalog must be attached with quotation for technical evaluation.

Date:	
(Name):	
Place: Name of Firm/Company/Agency:	
GSTIN No.:	
Phone No:	
Email:	
(Signature of Authorized Person)	
Seal:	

A M